
versatile™ 4C Surface Mount Collar, SM06D 17¹/₁₆" ACTUAL - 32 $\frac{3}{8}$ " ACTUAL — DEPTH 24½" ACTUAL $26\frac{1}{16}$ " FROM FINISHED FLOOR TO BOTTOM COLLAR FINISHED FLOOR

Notes:

- Designed to mount Florence Versatile[™] 4C mailbox double column 6-High Suite modules (sold separately).
- 2. For use with front loading modules only.

PRODUCT SERIES:	VERSATILETM 4C S	SURFACE MOUN	T COL	LAR		
			MODEL		I DEV	,
			MODEL	SM06D	REV	В
			SCALE	NONE		T REV DATE 7/02/2014
			DRAWIN	G NUMBER	•	DRAWN BY
•				SM06DCS		TNS

versatile™ 4C Mailbox, 4C06D-10



COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H x 12" W x 15" D	10
OUTGOING MAIL	OM2	6-1/2" H x 12" W x 15" D	1

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

MODEL 4C06D-10 REV	С
SCALE NONE LAST	6/27/19
DRAWING NUMBER	DRAWN BY
4C06D-10CS	RAK