# versatile™ 4C Surface Mount Collar, SM13S 17<sup>1</sup>½" ACTUAL $\rightarrow$ 18 $\frac{5}{16}$ " ACTUAL | **DEPTH** 48<sup>15</sup>/<sub>16</sub>" ACTUAL $13\frac{1}{16}$ " FROM FINISHED FLOOR TO BOTTOM OF COLLAR FINISHED FLOOR

### Notes:

- Designed to mount Florence Versatile<sup>™</sup> 4C mailbox single column 13-High Suite modules (sold separately).
- 2. For use with front loading modules only.

PRODUCT SERIES:	VERSATILE™ 4C SURFACE MOUNT COLLAR				
		MODEL (	SM13S	REV	В
		SCALE	NONE	LAS	T REV DATE 7/02/2014
		DRAWING	G NUMBER		DRAWN BY
		5	SM13SCS		TNS

# versatile™ 4C Mailbox, 4C13S-06 17" R.O. - 17 1/2" ACTUAL 16 1/2" MAX R.O. 16 1/4" MIN 47 3/4" 47 1/8" MAX R.O. 46 7/8" MIN 58 1/4" **ACTUAL** (TO TENANT LOCK) 40 3/4" (TO ACCESS LOCK) 15" 14 1/8" (TO BOTTOM FROM FINISHED FLOOR SHELF) TO BOTTOM OF R.O. FINISHED FLOOR

# COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H x 12" W x 15" D	6
OUTGOING MAIL	OM2	6-1/2" H x 12" W x 15" D	1
PARCEL	PL5	17" H x 12" W x 15" D	1

## Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
  - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
  - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
  - c. No patron (tenant) lock shall be positioned more than 67" AFF.
  - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
  - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

MODEL 40	C13S-06	REV	В
SCALE	NONE	LAS	t rev date 06/27/19
DRAWING	NUMBER		DRAWN BY
4C	13S-06CS		RAK