


Notes

- Designed to mount Florence Versatile[™] 4C mailbox double column 14-High Suite modules (sold separately).
- 2. For use with front loading modules only.

PRODUCT SERIES: VERSATILETM 4C SURFACE MOUN	VERSATILE™ 4C SURFACE MOUNT COLLAR				
	MODEL SA	M14D	REV	В	
	SCALE	NONE	LAS 0	T REV DATE 7/02/2014	
	DRAWING	NUMBER		DRAWN BY	
	SV	M14DCS		TNS	

versatile™ 4C Mailbox, 4C14D-14



COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H x 12" W x 15" D	14
OUTGOING MAIL	OM2	6-1/2" H x 12" W x 15" D	1
PARCEL	PL6	20-1/2" H x 12" W x 15" D	2

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

MODEL 40	C14D-14	REV	В
SCALE	NONE	07/08/19	
DRAWING	NUMBER		DRAWN BY
4C	14D-14CS		RAK